





PRB ACCROFIX PÂTE UV

UV RESISTANT PASTE-FORM ROUGH COAT



The of PRB ACCROFIX PÂTE UV

-  Protects from UVs (avoids the deterioration of the EPS)
-  Micro rough coat, used to fix a render mortar to an EPS
-  Provides adherence between the substrate and the finishing render
-  Easy to use (roller/brush/gun)

Ready-to-use

PACKAGING

- 20 kg tub.
- 0.48 t pallet, i.e. 24 20 kg tubs.

STORAGE: 24 months.

CONSUMPTION

Consumption is from 0.6 to 0.8 kg/m².

COLOUR: Grey.



AREA OF USE

USE

- EPS
- DTU20.1, DTU23.1, DTU 26.1.

AUTHORISED SUBSTRATES

- EPS Roller shutter box.
- EPS
- Other substrates (please contact us).

PROHIBITED SUBSTRATES

- On the ground.
- All Gypsum-based substrates (Plaster).
- Horizontal or pitched surfaces (except arches and undersides).

ASSOCIATED COATINGS

- PRB Fondisol F.
- Render mortars.

APPLICATION CONDITIONS

- Between 5°C and 35°C.
- Do not apply on substrates that are frozen or thawing, hot or exposed to full sunlight, soaked or exposed to driving rain and heavy winds.

TECHNICAL SPECIFICATIONS

COMPOSITION

- Synthetic resins.
- Mineral fillers.
- Specific additives.

PRODUCTS

- PASTE:**
- Density: 1.5 ± 0.1
 - pH (alkaline): 8.5 ± 0.5
 - Appearance: grey.

HARDENED:

- Adherence to EPS: > 0.08 MPa

APPLICATION

SUBSTRATE PREPARATION

- The substrates must be healthy, clean, cohesive and free from any residue or other substances that may be harmful to the correct adherence of the rough coat.
- The substrates must not bleed moisture.

APPLICATION

- Manual**
- PRB ACCROFIX PÂTE UV is applied using a roller, a brush or a gun.
 - The application of a coat of PRB FONDISOL F is recommended before applying the renders.
 - Tools are to be cleaned using clean water before the product has dried.

DRYING

- From 1 to 24 hours depending on weather conditions.

PRECAUTIONS FOR USE

- Read the regulatory labelling on the package and read the safety data sheet before using.