

# PRB SR ADDITIF

DRYING ACCELERATOR FOR FINISHING PRODUCTS



## The PRB SR ADDITIF

- + Forms a surface film allowing quick drying of TPC, TMC, paints and PRB FONDISOL PE
- + Ideal in wet and cold weather

### PACKAGING

- Box of 30 plastic 250 ml containers.

**STORAGE:** 12 months.

### CONSUMPTION

- 1 dose of 250 ml for 17 to 25 kg bucket

**COLOUR:** From clear to slightly yellow.

Ready-to-use

## AREA OF USE

### USE

- PRB SR ADDITIF is used on interior and exterior walls.

### DEFINITION

PRB SR ADDITIF is a liquid additive designed to speed up drying and form a surface film thereby protecting PRB finishes from the rain.

### APPLICATION CONDITIONS

- Between 1°C and 15°C

### IT MUST NOT BE USED:

- During frosts, at temperatures below 1°C.
- On frozen or thawing masonry.
- In hot spells in excess of 15°C
- In strong winds (dry or not) or in rain.

### PRECAUTIONS FOR USE

- PRB SR ADDITIF in high doses can cause risks of altering TMC characteristics.

## TECHNICAL CHARACTERISTICS

### PRODUCTS

- Appearance: liquid
- Colour: from clear to slightly yellow
- Density:  $1.05 \pm 0.05$
- pH:  $10.5 \pm 0.5$

## PREPARATION

After the addition of PRB SR ADDITIF, it is essential to quickly mix the whole using a mixer at a maximum speed of 300 rpm.

PRB SR ADDITIVE  
PAINT AND TPC ADDITIVE

PAINTER &  
FLOOR SPECIALIST